

Vault™ tech specs

BATTERY	LiPolymer (LiPo) 3.8 V, 4,000 mAh	<ul style="list-style-type: none"> Standard masking: 2+ days Maximum masking: ~6 hours Charge time: ~3 hours¹
DIMENSIONS	<ul style="list-style-type: none"> Exterior: 189.91 mm (7.47 inches) x 30.58 mm (1.20 inches) x 109.95 mm (4.32 inches) Interior: 162.32 mm (6.39 inches) x 10.54 mm (0.41 inches) x 82.14 mm (3.23 inches) 	<ul style="list-style-type: none"> Compatible with mobile devices up to 158.5 mm (6.24 inches) x 8.5 mm (.33 inches) x 78.5 mm (3.09 inches)
WEIGHT	0.47 kg (1.05 lbs)	
AUDIO	<ul style="list-style-type: none"> Digital signal processor for optimum audio quality and secure voice masking Masks speech intelligibility up to voice level of 90 dBA² 	<ul style="list-style-type: none"> Masks speech presence up to voice level of 80 dBA²
RF ATTENUATION	A minimum of 100 dB of RF attenuation from 500 MHz to 6 GHz	
PORT	USB-C charging port	
SWITCHES	Audio masking switch <ul style="list-style-type: none"> Controls audio masking level 	LED cover switch <ul style="list-style-type: none"> Blocks LEDs
UI-LEDS	Corner Indicator LEDs <ul style="list-style-type: none"> Protected Mode: Green Unprotected Mode: Red Voice Passthrough Mode (camera protection remains engaged): Red Checked-In Mode: Blue 	Power LEDs <ul style="list-style-type: none"> Displays battery power level and charging status
MOUNT	Built-in ¼" - 20 mounting screw	

¹ Tested with a 2A charger. ² Tested one meter from audio source.

